

POWERdrive

POWERdrive's dynamic response can be tuned to fit any content - from exceptionally smooth fades in architecture to fast-paced video in entertainment. This constant current LED driver is DMX/RDM/DALI compatible, and allows you to create your colour or dynamic show without an external controller. Symbiosis ensures the LED driver works seamlessly together with LED modules, controls and intelligent luminaire elements.


Product offering



POWERdrive 45/D

Part number P/N	PWR045D2
Product description	POWERdrive DC, 45W, DMX/RDM/DALI, 4 control channels, constant current, 4x LED outputs, plastic long

Order number configurator



P/N	LED driver part number.
-----	-------------------------

Warranty

Warranty period	General Terms and Conditions
-----------------	--

Project name:	Contact details:
Project number:	
LED driver order number:	

Electrical specifications

Driver type	constant current
Number of LED outputs	4 (UL Class 2)
Maximum LED output power	45W
Programmable LED output current range	200-500mA
LED output type	programmable in 50mA steps via user interface on driver programmable in 1mA steps via DMX terminal and FluxTool
LED output voltage range	11-31V (Vsup - 1V)
Nominal input voltage range DC	12-32V
Control protocol	DMX/RDM/DALI
Control channels	4

Dimensions, weight, packaging

Length (L)	typical: 193 mm / 7.6 in
Width (W)	typical: 50 mm / 1.97 in
Height (H)	typical: 23 mm / 0.91 in
Weight	191 g
Products per box	12 pcs

Connector layout



Certifications



Europe, Rest of World

eldoLED B.V.
Science Park Eindhoven 5125
5692 ED Son
The Netherlands

E: info@eldoled.com
W: www.eldoled.com

North America

eldoLED America
One Lithonia Way
Conyers, GA 30012
USA

E: info@eldoled.com
W: www.eldoled.com
