

## POWERdrive

POWERdrive's dynamic response can be tuned to fit any content - from exceptionally smooth fades in architecture to fast-paced video in entertainment. This constant current LED driver is DMX/RDM/DALI compatible, and allows you to create your colour or dynamic show without an external controller. Symbiosis ensures the LED driver works seamlessly together with LED modules, controls and intelligent luminaire elements.


## Product offering



### POWERdrive 180/D

Part number P/N	PWR180D2
Product description	POWERdrive DC, 180W, DMX/RDM/DALI, 4 control channels, constant current, 4x LED outputs, plastic long

## Order number configurator



P/N	LED driver part number.
-----	-------------------------

## Warranty

Warranty period	<a href="#">General Terms and Conditions</a>
-----------------	--

Project name:	Contact details:
Project number:	
LED driver order number:	

## Electrical specifications

Driver type	constant current
Number of LED outputs	4 (UL Class 2)
Maximum LED output power	180W
Programmable LED output current range	200-1,400mA
LED output type	programmable in 50mA steps via user interface on driver programmable in 1mA steps via DMX terminal and FluxTool
LED output voltage range	11-31V (Vsup - 1V)
Nominal input voltage range DC	12-32V
Control protocol	DMX/RDM/DALI
Control channels	4

## Dimensions, weight, packaging

Length (L)	typical: 193 mm / 7.6 in
Width (W)	typical: 50 mm / 1.97 in
Height (H)	typical: 23 mm / 0.91 in
Weight	191 g
Products per box	12 pcs

## Connector layout



---

**Certifications**

---



---

**Europe, Rest of World**

eldoLED B.V.  
Science Park Eindhoven 5125  
5692 ED Son  
The Netherlands

E: [info@eldoled.com](mailto:info@eldoled.com)  
W: [www.eldoled.com](http://www.eldoled.com)

---

**North America**

eldoLED America  
One Lithonia Way  
Conyers, GA 30012  
USA

E: [info@eldoled.com](mailto:info@eldoled.com)  
W: [www.eldoled.com](http://www.eldoled.com)

---