



USBTM
VISION **GEN*i*CAM**



sensor information	
sensor	Sony IMX267
resolution	4096 × 2160 px
exposure time	0,001 ... 60000 ms
pixel size	3.45 × 3.45 μm
shutter type	Global shutter
sensor type	1" CMOS
acquisition formats	
image formats, interface	Full Frame, 4096 × 2160 px, max. 39 fps
frame rate max.	Binning 2×2, 2048 × 1080 px, max. 39 fps Binning 2×1, 2048 × 2160 px, max. 39 fps Binning 1×2, 2048 × 1080 px, max. 39 fps
image formats, acquisition	Full Frame, 4096 × 2160 px, max. 40 fps
frame rate max. (Burst Mode)	
pixel formats	Mono8 Mono10 Mono12 Mono12 Packed
image preprocessing	
analog controls	Gain (0 ... 48 dB) Offset (0 ... 255 LSB 12 Bit)
color models	Mono
interfaces and connectors	
data interface	USB 3.0, Transfer Rate 5000 Mbits/sec, Connector: USB 3.0 Micro B
process interface	M8 / 8 pins (SACC-DSI-M8MS-8CON-M8-L180)
power supply	via USB 3.0 interface
mechanical data	
lens mount	C-mount
width	29 mm
height	29 mm
depth	38 mm

mechanical data	
weight	≤ 90 g
material	zinc die casting, nickel-plated, IP 40
electrical data	
power consumption	approx. 3,4 W @ 39 fps
operating voltage	5 VDC (via USB3.0 interface)
non-volatile memory	
flash memory size	128 kB
environmental conditions	
operating temperature	+5 ... +65 °C @ T = measurement point
humidity	10 ... 90 % (non-condensing)
protection class	IP 40
digital I/Os	
lines	1 input line 1 output line 2 general purpose lines
conformity	
conformity	CE RoHS EAC

VCXU-91M

USB 3.0, 8,9 Megapixel, Monochrome

Article number: 11173817

dimension drawing

