



**GIG** VISION **GEN<i>i</i>CAM**



#### sensor information

sensor	Sony IMX267
resolution	4096 × 2160 px
exposure time	0,001 ... 60000 ms
pixel size	3.45 × 3.45 µm
shutter type	Global shutter
sensor type	1" CMOS

#### acquisition formats

image formats, interface	Full Frame, 4096 × 2160 px, max. 13 fps
frame rate max.	Binning 2×2, 2048 × 1080 px, max. 21 fps Binning 2×1, 2048 × 2160 px, max. 21 fps Binning 1×2, 2048 × 1080 px, max. 21 fps

image formats, acquisition	Full Frame, 4096 × 2160 px, max. 21 fps
frame rate max. (Burst Mode)	

pixel formats	BayerRG8 BayerRG10 BayerRG12 BayerRG12 Packed Mono8 Mono10 Mono12 Mono12 Packed RGB8 BGR8
---------------	--

#### image preprocessing

color models	Mono Raw Bayer RGB
--------------	--------------------------

#### interfaces and connectors

data interface	Gigabit Ethernet, Transfer rate 1000 Mb/s/sec, Fast Ethernet, Transfer Rate 100 Mb/s/sec, Connector: 8P8C Modular Jack (RJ45), screwable type
process interface	M8 / 8 pins (SACC-DSI-M8MS-8CON-M8-L180)

#### interfaces and connectors

power supply	M8 / 8 pins or PoE
--------------	--------------------

#### mechanical data

lens mount	C-mount
width	29 mm
height	29 mm
depth	49 mm
weight	≤ 120 g
material	zinc die casting, nickel-plated, IP 40

#### electrical data

voltage supply	12 ... 24 V DC (external power supply)
range +Vs	36 ... 57 V DC (Power over Ethernet)
power consumption	approx. 2,6 W @ 12 VDC and 13 fps approx. 3,2 W @ 48 VDC (PoE) and 13 fps

#### non-volatile memory

flash memory size	128 kB
-------------------	--------

#### environmental conditions

operating temperature	+5 ... +65 °C @ T = measurement point
humidity	10 ... 90 % (non-condensing)
protection class	IP 40

#### digital I/Os

lines	1 input line 1 output line 2 general purpose lines
-------	--

#### conformity

conformity	CE RoHS EAC
------------	-------------------

# VCXG-91C

Gigabit Ethernet, 8,8 Megapixel, Color

Article number: 11173819

## dimension drawing

