

overview

- 1392 × 1040 px
- Sony ICX285
- 2/3" CCD
- 30 fps
- Gigabit Ethernet
- Phase-Out starting 04/19, alternative via sales



technical data

sensor information

sensor	Sony ICX285
resolution	1392 × 1040 px
exposure time	0,004 ... 60000 ms
pixel size	6.45 × 6.45 µm
shutter type	Global shutter
sensor type	2/3" CCD

acquisition formats

image formats, interface frame rate max.	Full Frame, 1392 × 1040 px, max. 30 fps Full Frame HQ, 1392 × 1040 px, max. 15 fps Binning 2×2 HQ, 696 × 520 px, max. 30 fps Binning 2×2, 696 × 520 px, max. 60 fps Binning 1×2 HQ, 1392 × 520 px, max. 30 fps Binning 1×2, 1392 × 520 px, max. 60 fps Binning 2×1 HQ, 696 × 1040 px, max. 15 fps Binning 2×1, 696 × 1040 px, max. 30 fps
--	--

pixel formats	Mono8 Mono12 Mono12 Packed
---------------	----------------------------------

image preprocessing

analog controls	Gain (0 ... 20 dB) Offset (0 ... 1023 LSB 14 Bit)
color models	Mono

camera features

synchronization	free running trigger sequencer
trigger sources	Hardware software ActionCommand
trigger delay	0 ... 2 sec, tracking and buffering of up to 512 trigger signals
sequencer	Automated control for series of images using different sets of parameters
sequencer parameter	exposure time gain factor
digital inputs	1 input line (with Debouncer)
digital outputs	1 output line
internal image buffer	32 MB

interfaces and connectors

data interface	Gigabit Ethernet, Transfer rate 1000 Mbts/sec, Connector: 8P8C Modular Jack (RJ45), screwable type
process interface	M8 / 4 pins
power supply	M8 / 3 pins

mechanical data

lens mount	C-mount
width	36 mm
height	36 mm
depth	48 mm
weight	≤ 90 g

technical data

mechanical data

material housing: aluminum

electrical data

voltage supply range +Vs 8 ... 30 V DC

power consumption approx. 5,0 W

environmental conditions

operating temperature +5 ... +50 °C

humidity 10 ... 90 % (non-condensing)

environmental conditions

protection class IP 40

conformity

conformity CE
RoHS
FCC
UL

dimension drawing

