

**overview**

- 1384 × 1036 px
- Sony ICX267
- 1.2" CCD
- 20 fps
- Gigabit Ethernet
- Phase-Out starting 04/19, alternative via sales



**technical data**

sensor information		camera features	
sensor	Sony ICX267	synchronization	free running trigger
resolution	1384 × 1036 px	trigger sources	Hardware software ActionCommand
exposure time	0,004 ... 60000 ms	trigger delay	0 ... 2 sec, tracking and buffering of up to 512 trigger signals
color filter	RGB Bayer Mosaic	digital inputs	1 input line (with Debouncer)
pixel size	4.65 × 4.65 µm	digital outputs	1 output line
shutter type	Global shutter	internal image buffer	32 MB
sensor type	1.2" CCD	interfaces and connectors	
acquisition formats		data interface	Gigabit Ethernet, Transfer rate 1000 Mbits/sec, Connector: 8P8C Modular Jack (RJ45), screwable type
image formats, interface frame rate max.	Full Frame, 1384 × 1036 px, max. 20 fps Full Frame HQ, 1384 × 1036 px, max. 10 fps	process interface	M8 / 4 pins
pixel formats	Mono8 BayerRG8 BayerRG12 RGB8 Packed BGR8 Packed YUV411 Packed YUV422 Packed YUV444 Packed	power supply	M8 / 3 pins
image preprocessing		mechanical data	
analog controls	Gain (0 ... 20 dB) Offset (0 ... 255 LSB 12 Bit)	lens mount	C-mount
color models	RGB YUV Mono	width	36 mm
color processing	Integrated color processor for high quality color calculation	height	36 mm
		depth	48 mm
		weight	≤ 90 g
		material	housing: aluminum
		electrical data	
		voltage supply range +Vs	8 ... 30 V DC
		power consumption	approx. 4,0 W

**technical data**

**environmental conditions**

operating temperature	+5 ... +50 °C
humidity	10 ... 90 % (non-condensing)
protection class	IP 40

**conformity**

conformity	CE
	RoHS
	FCC
	UL

**dimension drawing**

