



sensor information

sensor	Sony IMX287
resolution	720 × 540 px
exposure time	0,001 ... 60000 ms
pixel size	6.9 × 6.9 μm
shutter type	Global shutter
sensor type	1/2.9" CMOS

acquisition formats

image formats, interface	Full Frame, 720 × 540 px, max. 318 fps
frame rate max.	Binning 2×2, 360 × 270 px, max. 436 fps Binning 2×1, 360 × 540 px, max. 436 fps Binning 1×2, 360 × 270 px, max. 436 fps

image formats, acquisition	Full Frame, 720 × 540 px, max. 441 fps
frame rate max. (Burst Mode)	

pixel formats	BayerRG8 BayerRG10 BayerRG12 BayerRG12 Packed Mono8 Mono10 Mono12 Mono12 Packed RGB8 BGR8
---------------	--

image preprocessing

color models	Mono Raw Bayer RGB BGR
--------------	---------------------------------

interfaces and connectors

data interface	Gigabit Ethernet, Transfer rate 1000 Mbts/sec, Fast Ethernet, Transfer Rate 100 Mbts/sec, Connector: 8P8C Modular Jack (RJ45), screwable type
----------------	---

interfaces and connectors

process interface	M8 / 8 pins (SACC-DSI-M8MS-8CON-M8-L180)
power supply	M8 / 8 pins or PoE

mechanical data

lens mount	C-mount
width	29 mm
height	29 mm
depth	49 mm
weight	≤ 120 g
material	zinc die casting, nickel-plated, IP 40

electrical data

power consumption	approx. 2,3 W @ 12 VDC und 318 fps approx. 3,1 W @ 48 VDC (PoE) and 318 fps
-------------------	--

non-volatile memory

flash memory size	128 kB
-------------------	--------

environmental conditions

operating temperature	+5 ... +65 °C @ T = measurement point
humidity	10 ... 90 % (non-condensing)
protection class	IP 40

digital I/Os

lines	1 input line 1 output line 2 general purpose lines
-------	--

conformity

conformity	CE RoHS EAC
------------	-------------------

VCXG-04C

Gigabit Ethernet, 0,4 Megapixel, Color

Article number: 11183217

dimension drawing

