

overview

- 4096 × 2160 px
- Sony IMX255
- 1" CMOS
- 42 fps
- USB 3.0
- available



technical data

sensor information

sensor	Sony IMX255
resolution	4096 × 2160 px
exposure time	0,001 ... 60000 ms
pixel size	3.45 × 3.45 μm
shutter type	Global shutter
sensor type	1" CMOS

acquisition formats

image formats, interface frame rate max.	Full Frame, 4096 × 2160 px, max. 41 fps Binning 2×2, 2048 × 1080 px, max. 160 fps Binning 2×1, 2048 × 2160 px, max. 43 fps Binning 1×2, 2048 × 1080 px, max. 43 fps
--	--

pixel formats

- Mono8
- Mono10
- Mono12
- Mono12 Packed

image preprocessing

analog controls	Gain (0 ... 48 dB) Offset (0 ... 255 LSB 12 Bit)
color models	Mono

camera features

synchronization	free running trigger
trigger sources	Hardware software

camera features

trigger delay	0 ... 2 sec, tracking and buffering of up to 256 trigger signals
internal image buffer	330 MB 31 images (Trigger Mode) 1 image (Free Running Mode)

interfaces and connectors

data interface	USB 3.0, Transfer Rate 5000 Mbits/sec, Connector: USB 3.0 Micro B
process interface	M8 / 8 pins (SACC-DSI-M8MS-8CON-M8-L180)
power supply	via USB 3.0 interface

mechanical data

lens mount	C-mount
width	29 mm
height	29 mm
depth	38 mm
weight	≤ 90 g
material	zinc die casting, nickel-plated, IP 40

electrical data

power consumption	approx. 3,6 W @ 41 fps
operating voltage	5 VDC (via USB3.0 interface)

non-volatile memory

flash memory size	128 kB
-------------------	--------

environmental conditions

operating temperature	+5 ... +65 °C @ T = measurement point
humidity	10 ... 90 % (non-condensing)
protection class	IP 40

technical data

digital I/Os

lines
1 input line
1 output line
2 general purpose lines

conformity

conformity
CE
RoHS
EAC

dimension drawing

