



features

- dual port GigE PCIe x4 interface board with PoE support
- GigE cables 3,0 m
- 2x trigger/flash cable, 5,0 m
- power supply kit for LX, PX and VCXG cameras
- Mounting Adapter Type B (Tripod)
- Software (Windows®) via Download
- camera not included

interface card

| | |
|----------------|--|
| article number | 11168453 |
| name | PCI-1672PC Dual PoE (ZVA-PCIe-1672PC) |
| features | <ul style="list-style-type: none"> ▪ 2 port GigE to PCI Express host adapter ▪ RJ45 connector ▪ chipset: Intel® I350-AM2 ▪ Power over Ethernet, IEEE 802.3af compliant, support class 0, 1, 2, 3, and 4, provides up to 15,4 Watt ▪ tested Jumbo Frames: 9 kByte ▪ Note: 4 lane PCI Express connector required |

cable

| | |
|----------------|---|
| article number | 10170048 |
| name | cable GigE RJ45/RJ45, 3,0 m |
| features | <ul style="list-style-type: none"> ▪ GigE cable ▪ RJ45/RJ45 ▪ CAT7 ▪ length 3,0 m |

process interface cable

| | |
|----------------|---|
| article number | 11004523 |
| name | cable 8 wires, 5,0 m (ESG 32FH0500) |
| features | <ul style="list-style-type: none"> ▪ cable ▪ M8 female connector ▪ 8-pin ▪ open wires at one side ▪ cable carrier compatible ▪ length 5,0 m |
| article number | 11118799 |
| name | cable 8 wires, 5,0 m (Z-KSG 32FP0500G) |

process interface cable

| | |
|----------|---|
| features | <ul style="list-style-type: none"> ▪ shielded cable ▪ M8 male connector ▪ 8 pole ▪ open wires at one side ▪ cable carrier compatible ▪ length 5,0 m |
|----------|---|

power supply

| | |
|----------------|---|
| article number | 11122415 |
| name | Power Supply Kit LX PX VCXG int. |
| features | <ul style="list-style-type: none"> ▪ power supply 12V/2,0A international with adapters for EU, US, UK, AU, KR and power supply and process interface adapter cable for LX, PX and VCXG cameras ▪ length 5,0 m |

fixing

| | |
|----------------|---|
| article number | 11003060 |
| name | Mounting Adapter Type B (Tripod) |
| features | <ul style="list-style-type: none"> ▪ easy camera mounting ▪ robust anodized surface ▪ stable lightweight metal design (aluminium, 17g) ▪ UNC ¼"- 20 thread for mounting (tripod thread) |