



features

- Gigabit Ethernet PCI Express interface board
- Gigabit Ethernet cable 3,0 m
- trigger/flash cable, 5,0 m
- international power supply 12V/2,0A, cable length 1,8 m
- Mounting Adapter Type A (Front)
- Mounting Adapter Type B (Tripod)
- Software (Windows®, Linux®, Linux® ARM®) via Download
- camera not included

interface card

article number	11137188
name	PCIe Ethernet Server Adapter I210-T1 (ZVA-PCIe_Intel_Eth_Server_Adptr_I1210-T1)
features	<ul style="list-style-type: none"> ▪ 1 port GigE to PCI Express host adapter ▪ RJ45 connector ▪ chipset: Intel® i210 Gigabit Controller ▪ tested Jumbo Frames: 9 kByte ▪ 1 lane interface

cable

article number	10170048
name	cable GigE RJ45/RJ45, 3,0 m
features	<ul style="list-style-type: none"> ▪ GigE cable ▪ RJ45/RJ45 ▪ CAT7 ▪ length 3,0 m

process interface cable

article number	10170032
name	shielded cable 4 wires, 5,0 m
features	<ul style="list-style-type: none"> ▪ shielded cable ▪ M8 female connector ▪ 4-pin ▪ open wires at one side ▪ cable carrier compatible ▪ length 5,0 m

power supply

article number	11044200
name	power supply 12V/2,0A intern.
features	<ul style="list-style-type: none"> ▪ international power supply 12V/2,0A with M8/3-pin female connector ▪ length 1,8 m ▪ adapter for EU, US, UK, AU and KR

fixing

article number	11002638
name	Mounting Adapter Type A (Front)
features	<ul style="list-style-type: none"> ▪ easy front side camera mounting ▪ robust anodized surface ▪ stable lightweight metal design (aluminium, 18 g)
article number	11003060
name	Mounting Adapter Type B (Tripod)
features	<ul style="list-style-type: none"> ▪ easy camera mounting ▪ robust anodized surface ▪ stable lightweight metal design (aluminium, 17g) ▪ UNC ¼"- 20 thread for mounting (tripod thread)