



features

- dual port GigE PCIe x4 interface board with PoE support
- GigE cables 3,0 m (2 pieces)
- trigger/flash cable, 5,0 m
- power supply kit for LX, PX and VCXG cameras
- Mounting Adapter Type B (Tripod)
- Software (Windows®, Linux®, Linux® ARM®) via Download
- camera not included

interface card

article number	11168453
name	PCI-1672PC Dual PoE (ZVA-PCIe-1672PC)
features	<ul style="list-style-type: none"> ▪ 2 port GigE to PCI Express host adapter ▪ RJ45 connector ▪ chipset: Intel® I350-AM2 ▪ Power over Ethernet, IEEE 802.3af compliant, support class 0, 1, 2, 3, and 4, provides up to 15,4 Watt ▪ tested Jumbo Frames: 9 kByte ▪ Note: 4 lane PCI Express connector required

cable

article number	10170048
name	2x cable GigE RJ45/RJ45, 3,0 m
features	<ul style="list-style-type: none"> ▪ GigE cable ▪ RJ45/RJ45 ▪ CAT7 ▪ length 3,0 m

process interface cable

article number	11004523
name	cable 8 wires, 5,0 m (ESG 32FH0500)
features	<ul style="list-style-type: none"> ▪ cable ▪ M8 female connector ▪ 8-pin ▪ open wires at one side ▪ cable carrier compatible ▪ length 5,0 m

power supply

article number	11122415
name	Power Supply Kit LX PX VCXG int.

power supply

features	<ul style="list-style-type: none"> ▪ power supply 12V/2,0A international with adapters for EU, US, UK, AU, KR and power supply and process interface adapter cable for LX, PX and VCXG cameras ▪ length 5,0 m
----------	---

fixing

article number	11003060
name	Mounting Adapter Type B (Tripod)
features	<ul style="list-style-type: none"> ▪ easy camera mounting ▪ robust anodized surface ▪ stable lightweight metal design (aluminium, 17g) ▪ UNC ¼" - 20 thread for mounting (tripod thread)