

# Accessories

## Connectors and cables

### Connection cable M12, 8-pin, straight, shielded



#### Features

- Connection cable shielded with female connector M12, shielding on cap nut
- 8-pin version
- Cable coating PUR
- Halogen-free
- Suitable for flexible cable carriers
- UL listed, number E315836
- Temperature range -40...+80 °C (fixed installation)

#### Part number


10129332	Connection cable 5 m shielded with female connector M12, 8-pin, straight (ESG 34FH0500G)
10129333	Connection cable 10 m shielded with female connector M12, 8-pin, straight (ESG 34FH1000G)
10127844	Connection cable 2 m shielded with female connector M12, 8-pin, straight (ESG 34FH0200G)

#### Suitable for

EIL580-B, EIL580-B - Option 6301, EIL580P-B, EIL580P-SC, EIL580P-SQ, EIL580P-SY, EIL580P-T, EIL580-SC, EIL580-SQ, EIL580-SY, EIL580-T, EIL580-T - Option 6301, ExEIL580-B, ExEIL580P-B, ExEIL580P-SC, ExEIL580P-SY, ExEIL580P-T, ExEIL580-SC, ExEIL580-SY, ExEIL580-T, GI357, GIM500R

#### Terminal assignment

Female connector M12	Core colour
Pin 1	white
Pin 2	brown
Pin 3	green
Pin 4	yellow
Pin 5	grey
Pin 6	pink
Pin 7	blue
Pin 8	red
Connector Housing	Shield/Housing



#### Dimensions

