

overview

- Panel PC for VeriSens® incl. stylus
- German operating system



technical data

electrical data

input external power supply, 65 Watt, 19VDC, Schuko plug type F

mechanical data

lens mount 75 mm x 75 mm VESA mount
 dimensions 293 mm x 218 mm x 45 mm
 weight ≤ 2,7 kg
 material plastic
 aluminum

interface

ports Serial: 4 x COM port
 COM 1 /2: RS232, RJ50
 COM 3: RS232/422/485, DB-9, Pin9 with RI/5V/12V (selectable via BIOS)
 COM 4: RS232, DB-9, pin9 with RI/5V/12V (selectable via BIOS)
 USB: 4x USB 2.0, 1x USB 3.0
 Keyboard/Mouse: 1x Mini DIN PS/2
 LAN: 1 x Gigabit Ethernet via RJ-45 , Support of Wake on LAN
 Cash Drawer: 1x RJ12, supports 12V / 24V DC
 audio: 2W speaker x 2

technical data

display TFT LCD size: 10,4" resolution: 1024 x 768 touch screen: 5 wire resistive
 main board Processor: Celeron J1900 (4 cores, up to 2,42 GHz, max TDP 10 Watt) system memory: 1 x SO-DIMM DDR3L 1067/1333MHz, 4 GB, operating system: Windows POSReady 7
 storage HDD: 1 x 2.5" SATA HDD; 1 x mSATA Slot for SSD

environmental conditions

operating temperature 0 ... +40 °C
 conformity FCC
 CE
 WEEE
 RoHS
 protection class IP65 (Front)

dimension drawing

