


LIF-P | PG thread

Connectors

Metal connector, straight, fixed PG outer thread



Temperature:	-40°C ... +250°C
--------------	------------------

Material:	nickel-plated brass
-----------	---------------------

Protection class [acc. to EN 60529]:	IP0
--------------------------------------	-----



FLEXA No.	OD [mm]	Thread type	Conduit DI	Conduit OD	Ø I [mm]	Ø B [mm]	C [mm]	D [mm]	WS [mm]	Weight [kg/100]	PU [pcs.]
15801010007	10,0	PG7	7,0	10,0	5,9	16,0	10,0	26,0	15	1,600	50
15801014009	14,0	PG9	10,0	14,0	8,9	21,0	10,0	27,0	19	2,400	50
15801017011	17,0	PG11	13,0	17,0	12,0	25,0	10,0	27,0	23	3,100	50
15801019013	19,0	PG13,5	15,0	19,0	14,0	27,0	10,0	27,0	25	3,200	50
15801021016	21,0	PG16	17,0	21,0	15,9	29,0	10,0	27,0	27	3,900	50
15801027021	27,0	PG21	22,0	27,0	20,4	37,0	11,0	30,6	34	6,200	25
15801036029	36,0	PG29	29,0	36,0	27,5	45,6	13,0	33,0	43	8,800	25
15801045036	45,0	PG36	38,0	45,0	36,6	59,0	13,0	33,0	54	11,750	25
15801056048	56,0	PG48	49,0	56,0	47,5	69,0	13,5	33,5	66	16,400	10
15801410007	10,0	PG7	7,0	10,0	5,9	16,0	10,0	26,0	15	1,600	10
15801414009	14,0	PG9	10,0	14,0	8,9	21,0	10,0	27,0	19	2,400	10
15801417011	17,0	PG11	13,0	17,0	12,0	25,0	10,0	27,0	23	3,100	10
15801419013	19,0	PG13,5	15,0	19,0	14,0	27,0	10,0	27,0	25	3,200	10
15801421016	21,0	PG16	17,0	21,0	15,9	29,0	10,0	27,0	27	3,900	10
15801427021	27,0	PG21	22,0	27,0	20,4	37,0	11,0	30,6	34	6,200	10
15801436029	36,0	PG29	29,0	36,0	27,5	45,6	13,0	33,0	43	8,800	2
15801445036	45,0	PG36	38,0	45,0	36,6	59,0	13,0	33,0	54	11,750	2
15801456048	56,0	PG48	49,0	56,0	47,5	69,0	13,5	33,5	66	16,400	2

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.