

USB | metric thread


Connectors

Metal connector, safety-type, bend 90°, metric outer thread, incl. ferrule [brass], sealing and O-ring [NBR]

Temperature: -40°C ... +100°C

Material: nickel-plated brass

Protection class [acc. to EN 60529]: IP00



FLEXA No.	OD [mm]	Thread type	Conduit DI	Conduit OD	Ø I [mm]	Ø B [mm]	C [mm]	D [mm]	WS [mm]	Weight [kg/100]	PU [pcs.]
15025327016	17,0	M16 x 1,5	14,0	17,0	10,4	27,0	11,5	47,2	25	16,400	25
15025327020	21,0	M20 x 1,5	18,0	21,0	14,0	31,5	13,0	53,9	29	28,000	25
15025327025	27,0	M25 x 1,5	23,0	27,0	20,0	39,0	15,0	64,2	36	43,200	10
15025327032	36,0	M32 x 1,5	31,0	36,0	26,0	48,0	15,0	73,7	45	66,000	10
15025327040	45,0	M40 x 1,5	40,0	45,0	34,0	57,0	16,0	86,5	54	110,000	10
15025327050	56,0	M50 x 1,5	51,0	56,0	41,0	70,0	18,0	101,7	66	160,000	2

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.