

NIMS-M | metric thread


Connectors

Metal conduit olive, hexagon wrench surface, fixed metric outer thread, incl. O-Ring

Temperature: -40°C ... +250°C

Material: nickel-plated brass

Protection class [acc. to EN 60529]: IP 65



FLEXA No.	OD [mm]	Thread type	$\varnothing I$ [mm]	$\varnothing C$ [mm]	$\varnothing D$ [mm]	E [mm]	F [mm]	WS [mm]	Weight [kg/m]	PU [pcs.]
15010023012	14,0	M12 x 1,5	7,0	9,0	15,5	6,4	29,0	14	1,380	10
15010023016	17,0	M16 x 1,5	10,0	12,0	19,0	6,5	29,0	17	2,300	10
15010023020	19,0	M20 x 1,5	12,0	14,0	24,3	6,5	29,0	22	3,400	10
15010023025	21,0	M25 x 1,5	14,0	16,0	30,1	6,5	29,0	27	4,400	10
15010023032	27,0	M32 x 1,5	19,0	21,0	39,1	6,5	32,1	35	8,600	5
15010023040	36,0	M40 x 1,5	27,0	29,0	51,0	7,5	39,0	43	10,800	5
15010023050	45,0	M50 x 1,5	35,0	37,1	59,5	10,0	47,0	54	15,000	5
15010023063	56,0	M63 x 1,5	46,0	54,0	70,0	10,0	50,1	65	33,000	5

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.