

## NIMS-P | PG thread


## Connectors

Metal conduit olive, hexagon wrench surface, fixed PG outer thread, incl. O-Ring

**Temperature:** -40°C ... +250°C

**Material:** nickel-plated brass

**Protection class [acc. to EN 60529]:** IP 65



FLEXA No.	OD [mm]	Thread type	Ø I [mm]	Ø C [mm]	Ø D [mm]	E [mm]	F [mm]	WS [mm]	Weight [kg/m]	PU [pcs.]
15010022009	14,0	PG9	7,0	9,0	21,0	6,0	29,0	19	2,120	10
15010022011	17,0	PG11	10,0	12,0	24,0	6,0	29,0	22	3,200	10
15010022013	19,0	PG13,5	12,0	14,0	24,0	6,0	29,0	24	2,940	10
15010022016	21,0	PG16	14,0	16,0	26,0	6,0	29,0	24	3,500	10
15010022021	27,0	PG21	19,0	21,0	35,5	6,0	29,0	32	5,000	5
15010022029	36,0	PG29	27,0	29,0	44,0	8,0	39,0	41	13,930	5
15010022036	45,0	PG36	34,0	36,0	54,0	9,0	41,0	50	14,200	5

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.