

# PXN12C

 MULTI-CONTACT CONNECTORS 

10 A IP65/IP66



**WALL MOUNTING  
SOCKET PXN12C**



Wall box 30°  
06A0001



**PLUG PXN12C**



Plug  
06A1001

## MAIN FEATURES

Rated current (with wiring according to standard)	4-20 mA/10 A	Ambient temperature	-40 °C to +55 °C
Maximum voltage	220 V	Flexible wiring (min-max)	1-2,5 mm <sup>2</sup>
Number of contacts	11C+E	Wiring (terminals)	crimping
IP protection lid closed	IP65/IP66	Protection mode	e or i, tb
IP protection plug connected	IP65/IP66	ATEX zones	1 & 2, 21 & 22
Shock resistance	IK09	Keying positions	2

Connection or disconnection  
screw locking imprint BTR 2.5.

**WALL** mounting socket  
female  
**PXN12c (10 A)**



**PLUG** male  
**PXN12c (10 A)**



M25	06A000125M	9-16 mm	M25	06A100125M	9-16 mm
M32	06A0001	12-21 mm	M32	06A1001	12-21 mm

**INCLINED** socket  
female  
**PXN12c (10 A)**



**INCLINED**  
appliance inlet male  
**PXN12c (10 A)**



06A7001

06A9001

**COUPLER** socket  
female  
**PXN12c (10 A)**




**WALL** mounting  
appliance inlet male  
**PXN12c (10 A)**



M25	06A300125M	9-16 mm	M25	06A600125M	9-16 mm
M32	06A3001	12-21 mm	M32	06A6001	12-21 mm

MARECHAL ELECTRIC FRANCE

 II 2 G D Ex e IIC Gb Ex tb IIIC Db  
-40 °C ≤ Ta ≤ +55 °C T5 T69 °C  
Ex ia or ib IIC T6 Gb  
IECEX LCIE 14.0041X/LCIE 07 ATEX 6070X

**INFOS +**

Each product is supplied with 1 bag of 13 contacts depending on the maximum configuration.  
This allows you to set up the product to suit your needs.