



**WALL MOUNTING SOCKET DN1**



Wall box metal 20°  
593B2M25



Socket-outlet  
1914017

**PLUG DN1**



Straight handle poly  
513POD30



Inlet  
1918017

## MAIN FEATURES

Rated current (with wiring according to standard)	30 A	Ambient temperature	-40 °C to +60 °C
Maximum voltage	500 V	Flexible wiring (min-max)	2,5-6 mm²
IP protection lid closed	IP55	Stranded wiring (min-max)	2,5-10 mm²
IP protection plug connected	IP54	Other wiring	on request
Shock resistance (metal casing)	IK09	Keying positions	16

### Load-break capability of the DECONTACTOR™

Comply with IEC/EN 60309-1 and IEC/EN 60309-4 standards

30 A/500 V

Load-break capability according to IEC/EN 60947-3/AC-22 A

(30 A/400 V) or (16 A/500 V)

**SOCKET-OUTLET female DN1 (30 A)**



**INLET male DN1 (30 A)**



Dual-voltage socket-outlet (see p. 7)

20-24 V AC	2P	191408A	191808A
220-250 V AC	1P+N+E	1914015	1918015
380-440 V AC	3P+E	1914013	1918013
220-250 V AC	3P+N+E	1914017	1918017
480-500 V AC	3P+E	1914093	1918093
480-500 V AC	3P+N+E	1914097	1918097

► Other voltages, frequencies and contact configurations are available (see page 10).

## INFO+

### OPTIONS AND ACCESSORIES

Find the boxes, sleeves and handles at the end of the section page 64.

