



### WALL MOUNTING SOCKET DN3



Wall box metal 20°  
594B2M25



Socket-outlet  
1934017

### PLUG DN3



Straight handle poly  
514P0D35



Inlet  
1938017

## MAIN FEATURES

Rated current (with wiring according to standard)	50 A	Ambient temperature	-40 °C to +60 °C
Maximum voltage	500 V	Flexible wiring (min-max)	2,5-16 mm <sup>2</sup>
IP protection lid closed	IP55	Stranded wiring (min-max)	2,5-25 mm <sup>2</sup>
IP protection plug connected	IP54	Other wiring	on request
Shock resistance (metal casing)	IK09	Keying positions	16

### Load-break capability of the DECONTACTOR™

Comply with IEC/EN 60309-1 and IEC/EN 60309-4 standards	50 A/500 V
Load-break capability according to IEC/EN 60947-3/AC-22 A	(50 A/400 V) or (32 A/500 V)

### SOCKET-OUTLET female DN3 (50 A)



### INLET male DN3 (50 A)



Dual-voltage socket-outlet (see p. 7)

20-24 V AC	2P	193408A	193808A
220-250 V AC	1P+N+E	1934015	1938015
380-440 V AC	3P+E	1934013	1938013
220-250 V AC 380-440 V AC	3P+N+E	1934017	1938017
480-500 V AC	3P+E	1934093	1938093
480-500 V AC	3P+N+E	1934097	1938097

► Other voltages, frequencies and contact configurations are available (see page 10).

## INFO+

### OPTIONS AND ACCESSORIES

Find the boxes, sleeves and handles at the end of the section page 64.

