



WALL MOUNTING SOCKET DS7c3



Wall box metal 30°
594C3M32

Socket-outlet
3934561

PLUG DS7c3



Straight handle poly
514P0D35

Inlet
3938561

MAIN FEATURES

| | | | |
|---|-------|---------------------------|------------------------|
| Rated current (with wiring according to standard) | 50 A | Ambient temperature | -40 °C to +60 °C |
| Maximum voltage | 500 V | Flexible wiring (min-max) | 2,5-10 mm ² |
| IP protection lid closed | IP55 | Stranded wiring (min-max) | 2,5-10 mm ² |
| IP protection plug connected | IP54 | Wiring (terminals) | screw-type |
| Shock resistance (metal casing) | IK09 | Keying positions | 5 |
| Auxiliary contacts 5 A/400 V option | 3 | | |

Load-break capability of the DECONTACTOR™

| | |
|---|------------|
| Comply with IEC/EN 60309-1 and IEC/EN 60309-4 standards | 50 A/500 V |
| Load-break capability according to IEC/EN 60947-3/AC-22 A | 50 A/500 V |

SOCKET-OUTLET female DS7c3 (50 A)



INLET male DS7c3 (50 A)



| | | | |
|-------------------|-------------|------------|------------|
| 50 A/max 500 V AC | 6P+E | 3934561 | 3938561 |
| 50 A/max 500 V AC | 6P+E+3 aux. | 3934561972 | 3938561972 |

INFO+

OPTIONS AND ACCESSORIES

Find the boxes, sleeves and handles at the end of the section page 94.

