



### WALL MOUNTING SOCKET DB9



Wall box metal 70°  
595C7M50



Socket-outlet  
8794017

### PLUG DB9



Straight elastomer  
555POD35



Inlet  
8798017

## MAIN FEATURES

Rated current (with wiring according to standard)	125 A	Ambient temperature	-40 °C to +60 °C
Maximum voltage	690 V	Flexible wiring (min-max)	16-50 mm <sup>2</sup>
IP protection lid closed	IP66/IP67	Stranded wiring (min-max)	25-70 mm <sup>2</sup>
IP protection plug connected	IP66/IP67	Pre-wired auxiliary contacts (5 A)	1,5 mm <sup>2</sup>
Shock resistance	IK09	Keying positions	24

### Load-break capability of the DECONTACTOR™

Comply with IEC/EN 60309-1 and IEC/EN 60309-4 standards	125 A/690 V
Rated powers (AC-3 load-breaking capacity according to IEC/EN 60947-3):	15 kW up to 230 V - 1P 22 kW up to 230 V - 3P 30 kW up to 400 V - 3P 30 kW up to 500 V - 3P 45 kW up to 690 V - 3P
Short-circuit current I <sub>cc</sub>	200 kA

### SOCKET-OUTLET female DB9 (125 A)



### INLET male DB9 (125 A)



220-250 V AC	1P+N+E	8794015	8798015
380-440 V AC	3P+E	8794013	8798013
220-250 V AC 380-440 V AC	3P+N+E	8794017	8798017
660-690 V AC	3P+E	8794193	8798193
380-400 V AC 660-690 V AC	3P+N+E	8794197	8798197
Auxiliaries 5 A/400 V AC	+ 4 contacts	Ref. + 264	Ref. + 264

► Other voltages, frequencies and contact configurations are available (see page 10).

## INFO+

### OPTIONS AND ACCESSORIES

Find the boxes, sleeves and handles at the end of the section page 77.

