

USDR-M | metric thread


Connectors

Metal connector, safety-type, straight, turnable metric outer thread, incl. ferrule [brass], sealing [TPE] and O-ring [NBR]

Temperature: -40°C ... +125°C

Material: nickel-plated brass

Protection class [acc. to EN 60529]: IP00



FLEXA No.	OD [mm]	Thread type	Conduit DI	Conduit OD	Ø I [mm]	Ø B [mm]	C [mm]	D [mm]	WS1 [mm]	WS2 [mm]	Weight [kg/100]	PU [pcs.]
15013327012	10,0	M12 x 1,5	8,0	10,0	6,5	19,0	10,0	28,0	15	17	2,400	10
15013339016	14,0	M16 x 1,5	12,0	14,0	9,0	23,0	10,0	30,0	21	21	5,000	10
15013327020	17,0	M20 x 1,5	14,0	17,0	11,0	27,0	10,0	30,0	24	25	6,400	10
15013327025	21,0	M25 x 1,5	18,0	21,0	14,5	31,0	11,0	31,0	30	29	9,500	10
15013339032	27,0	M32 x 1,5	24,0	27,0	21,0	39,0	13,0	38,0	36	36	14,900	10
15013327040	36,0	M40 x 1,5	31,0	36,0	27,5	48,0	13,0	42,0	46	45	23,900	2
15013327050	45,0	M50 x 1,5	40,0	45,0	35,5	57,0	14,0	50,0	55	54	36,200	2
15013327063	56,0	M63 x 1,5	51,0	56,0	45,0	70,0	14,0	54,0	70	66	61,000	2

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.