


USZ-M | metric thread**Connectors**

Metal connector, safety-type, straight, metric outer thread, strain relief, incl. ferrule [brass], sealing [TPE] and O-ring [NBR]

Temperature: -40°C ... +100°C

Material: nickel-plated brass

Protection class [acc. to EN 60529]: IP5



FLEXA No.	OD [mm]	Thread type	Clamp.range [mm]	Conduit DI	Conduit OD	Ø I [mm]	Ø B [mm]	C [mm]	D [mm]	WS1 [mm]	WS2 [mm]	WS3 [mm]	Weight [kg/100]	PU [pcs.]
15016328112	10,0	M12 x 1,5	5,0-6,5	7,0	10,0	6,0	19,0	10,0	43,0	15	16	17	2,090	10
15016327116	14,0	M16 x 1,5	6,0-10,5	11,0	14,0	9,0	23,0	10,0	48,0	18	21	21	4,070	10
15016328120	17,0	M20 x 1,5	8,0-14,5	13,0	17,0	11,5	27,0	10,0	48,0	24	25	25	5,390	10
15016328020	21,0	M20 x 1,5	8,0-14,5	17,0	21,0	15,5	31,0	10,0	49,0	24	29	29	6,990	10
15016328125	21,0	M25 x 1,5	12,5-19,0	17,0	21,0	15,5	31,0	11,0	54,0	30	30	29	7,210	10
15016340025	27,0	M25 x 1,5	12,5-19,0	23,0	27,0	20,5	31,0	11,0	61,0	30	36	36	13,200	10
15016340132	27,0	M32 x 1,5	17,0-25,5	23,0	27,0	20,5	39,0	13,0	65,0	36	36	36	14,650	10
15016328140	36,0	M40 x 1,5	24,0-33,0	29,0	36,0	27,5	48,0	13,0	68,0	46	46	45	23,870	5
15016328150	45,0	M50 x 1,5	33,0-42,0	38,0	45,0	35,0	57,0	14,0	74,0	55	55	54	31,150	5
15016328163	56,0	M63 x 1,5	40,0-52,0	49,0	56,0	45,0	70,0	14,0	81,0	70	70	66	34,000	5

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.