

## USB | metric thread


## Connectors

Metal connector, safety-type, bend 90°, metric outer thread, incl. ferrule [brass], sealing and O-ring [NBR]

**Temperature:** -40°C ... +100°C

**Material:** nickel-plated brass

**Protection class [acc. to EN 60529]:** IP55



FLEXA No.	OD [mm]	Thread type	Conduit DI	Conduit OD	Ø I [mm]	Ø B [mm]	C [mm]	D [mm]	WS [mm]	Weight [kg/100]	PU [pcs.]
15025328016	17,0	M16 x 1,5	13,0	17,0	10,4	27,0	11,5	47,2	25	16,000	25
15025328020	21,0	M20 x 1,5	17,0	21,0	14,0	31,5	13,0	53,9	29	28,000	25
15025340025	27,0	M25 x 1,5	23,0	27,0	20,0	39,0	15,0	64,2	36	43,200	10
15025328032	36,0	M32 x 1,5	29,0	36,0	26,0	48,0	15,0	73,7	45	66,000	10
15025328040	45,0	M40 x 1,5	38,0	45,0	34,0	57,0	16,0	86,5	54	110,000	10
15025328050	56,0	M50 x 1,5	49,0	56,0	41,0	70,0	18,0	101,7	66	160,000	2

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.