

## USW-PG | PG thread


## Connectors

Metal connector, safety-type, 90° elbow, PG outer thread, incl. ferrule [brass], brass thrust collar [MSD] and O-ring [NBR]

Temperature: -40°C ... +250°C

Material: nickel-plated brass

Protection class [acc. to EN 60529] **IP4**



FLEXA No.	OD [mm]	Thread type	Conduit DI	Conduit OD	Ø I [mm]	Ø B [mm]	C [mm]	D [mm]	WS [mm]	Weight [kg/100]	PU [pcs.]
15011228009	14,0	PG9	10,0	14,0	8,5	23,0	9,0	41,0	21	3,600	25
15011235011	17,0	PG11	12,0	17,0	11,0	27,0	8,0	45,0	25	5,900	25
15011235013	19,0	PG13,5	14,0	19,0	13,0	29,0	10,0	49,5	27	7,700	25
15011235016	21,0	PG16	16,0	21,0	14,5	31,0	10,0	52,0	29	10,000	25
15011201021	27,0	PG21	21,0	27,0	19,5	39,0	10,5	58,0	36	13,400	10
15011228029	36,0	PG29	29,0	36,0	27,5	48,0	11,0	72,0	45	23,300	10

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.