


LKI-P | PG thread

Connectors

Plastic connector, straight, one-part, PG outer thread, turnable

Temperature: -10°C ... +110°C

Protection class [acc. to EN 60529] **IP4**



FLEXA No.	OD [mm]	Colour	Thread type	Ø I [mm]	Ø B [mm]	C [mm]	D [mm]	WS [mm]	Weight [kg/100]	PU [pcs.]
15020010007	10,0	Grey	PG7	5,5	17,5	10,0	38,0	16	0,300	50
15020010009	14,0	Grey	PG9	9,5	21,0	10,0	39,5	16	0,340	50
15020010011	17,0	Grey	PG11	11,5	24,5	10,0	42,0	22	0,600	50
15020010013	19,0	Grey	PG13,5	13,0	26,5	10,0	42,0	24	0,660	50
15020010016	21,0	Grey	PG16	14,5	30,0	11,0	48,0	27	0,920	50
15020010021	27,0	Grey	PG21	19,5	39,0	11,0	58,0	35	1,720	25
15020010029	36,0	Grey	PG29	27,0	50,0	12,0	59,0	45	2,800	25
15020010036	45,0	Grey	PG36	35,5	59,5	12,0	62,5	54	3,680	25
15020010048	56,0	Grey	PG48	46,0	71,5	15,0	68,0	65	5,800	10
15020710007	10,0	Grey	PG7	5,5	17,5	10,0	38,0	16	0,300	10
15020710009	14,0	Grey	PG9	9,5	21,0	10,0	39,5	19	0,340	10
15020710011	17,0	Grey	PG11	11,5	24,5	10,0	42,0	22	0,600	10
15020710013	19,0	Grey	PG13,5	13,0	26,5	10,0	42,0	24	0,660	10
15020710016	21,0	Grey	PG16	14,5	30,0	11,0	48,0	27	0,920	10
15020710021	27,0	Grey	PG21	19,5	39,0	11,0	58,0	35	1,720	10
15020710029	36,0	Grey	PG29	27,0	50,0	12,0	59,0	45	2,800	2
15020710036	45,0	Grey	PG36	35,5	59,5	12,0	62,5	54	3,680	2
15020710048	56,0	Grey	PG48	46,0	71,5	15,0	68,0	65	5,800	2

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.