


## MSD

## Connectors

Brass thrust collar, suitable for connectors US, for grounding and for shielding applications



Temperature: ... +250°C

Material: Messing



FLEXA No.	OD [mm]	ø D [mm]	ø d [mm]	L [mm]	Weight [kg/100]	PU [pcs.]
15031034007	10,0	13,0	10,2	5,0	0,160	50
15031034009	14,0	17,0	14,5	5,0	0,180	50
15031034011	17,0	21,0	17,2	5,0	0,320	50
15031034013	19,0	23,0	19,2	6,0	0,360	50
15031034016	21,0	25,0	21,3	6,0	0,400	50
15031034021	27,0	32,0	27,3	8,5	1,240	25
15031034029	36,0	41,0	36,3	8,5	1,400	25
15031034036	45,0	50,0	45,3	8,5	1,760	20
15031034048	56,0	61,0	56,3	8,5	2,200	10

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.