


EEK

## Connectors

Terminal sleeve | ferrule for connectors USK as terminal sleeve for protective conduits AIRflex

**Temperature:** -10°C ... +110°C

**Material:** plastics



FLEXA No.	OD [mm]	Conduitmaß [mm]	Ø l [mm]	Weight [kg/100]	PU [pcs.]
15020030007	10,0	7,0-10,0	6,0	0,040	50
15020030009	14,0	10,0-14,0	9,0	0,060	50
15020030011	17,0	13,0-17,0	11,5	0,100	50
15020030013	19,0	15,0-19,0	13,0	0,120	50
15020030016	21,0	16,0-21,0	14,5	0,140	50
15020030021	27,0	21,0-27,0	19,5	0,200	25
15020030029	36,0	29,0-36,0	26,5	0,400	25
15020030036	45,0	38,0-45,0	36,0	0,600	20
15020030048	56,0	48,0-56,0	45,5	0,770	10

Recommendations for any areas of applications, products, or product combinations are issued to the best of FLEXA's knowledge and experience. The user is requested to check applicability of FLEXA products to specific applications and purposes prior to the use of the particular products. All documentation, illustrations, and charts published are subject to copyright and must not be copied, changed, used, or modified. Technical drawings, certificates, authorizations, and results by the FLEXA lab will be provided upon request. FLEXA will not be held liable for typographical or other errors and incorrect drawings. Technical modifications are subject to change without prior notice.