



WALL MOUNTING SOCKET DB3



Wall box metal 70°
593C7M25



Socket-outlet
8734017

PLUG DB3



Straight handle poly
513P0D30



Inlet
8738017

MAIN FEATURES

Rated current (with wiring according to standard)	40 A	Ambient temperature	-40 °C to +60 °C
Maximum voltage	690 V	Flexible wiring (min-max)	2,5-6 mm ²
IP protection lid closed	IP66/IP67	Stranded wiring (min-max)	2,5-10 mm ²
IP protection plug connected	IP66/IP67	Pre-wired auxiliary contacts (5 A)	1,5 mm ²
Shock resistance	IK09	Keying positions	24

Load-break capability of the DECONTACTOR™

Comply with IEC/EN 60309-1 and IEC/EN 60309-4 standards	40 A/690 V
Rated powers (AC-3 load-breaking capacity according to IEC/EN 60947-3):	3 kW up to 230 V - 1P 5,5 kW up to 230 V - 3P 7,5 kW up to 400 V - 3P 7,5 kW up to 500 V - 3P 7,5 kW up to 690 V - 3P
Short-circuit current I _{cc}	200 kA

SOCKET-OUTLET female DB3 (40 A)



INLET male DB3 (40 A)



220-250 V AC	1P+N+E	8734015	8738015
380-440 V AC	3P+E	8734013	8738013
220-250 V AC 380-440 V AC	3P+N+E	8734017	8738017
660-690 V AC	3P+E	8734193	8738193
380-400 V AC 660-690 V AC	3P+N+E	8734197	8738197
Auxiliaries 5 A/400 V AC	+ 2 contacts	Ref. + 172	Ref. + 172

► Other voltages, frequencies and contact configurations are available (see page 10).

INFO+

OPTIONS AND ACCESSORIES

Find the boxes, sleeves and handles at the end of the section page 77.

